



**Reference Standard:** EN 14411: 2012 Ceramic Floor and Wall Tiles: Definitions, Classification, Characteristics and Marking

**Product Type:** Dry Pressed: Group BIII GL

**REVIGRÉS Reference:** UNICOLOR NAT

**Use:** Internal Wall Tiles

TEST METHODS	STANDARD AND TEST VALUE	DECLARED VALUES
Length and Width	ISO 10545-2	± 0,5%
Deviation of mean thickness from manufacturing thickness		± 10%
Straightness of the edges		± 0,3%
Orthogonality		± 0,5%
Surface Flatness		+ 0,5%
Surface quality (% defect free)		- 0,3%
Water Absorption	ISO 10545-3	≥ 95%
Bending Strength (N)	ISO 10545-4	Compliant
Rupture Modulus (N/mm <sup>2</sup> )	ISO 10545-4	> 10%
Coefficient of Linear Thermal expansion (with atmospheric temperature up to 100 °C)	ISO 10545-8	> 600
Cracking resistance (Glazed)	ISO 10545-11	> 15
Resistance to Acids and high concentrations Bases	ISO 10545-13	Test method available
Resistance to Acids and low concentrations Bases		Test method available
Resistance to household chemicals and swimming pool water additives		Test available
Resistance to staining	ISO 10545-14	Mín. Classe B
Reaction to fire	EN 13823 EN 9239-1	Test method available
		Min. Class 4
		A1 <sub>FL</sub>
		Class A1

\*Technical specifications are only valid for the products classified as 1<sup>st</sup> choice.

012/10

Quality Manager

2021.07.20