

PERFORMANCE STATEMENT

001UKCA_PorcelainTiles

1 – Unique identification code for product / type:

Glazed or unglazed dry pressed ceramic tiles, with water absorption less than 0.5% ($E_b \leq 0.5\%$).

2 – Use:

For internal or external, floor and wall.

3 – Name and address of manufacturer:

Revigrés, Indústria de Revestimentos de Grés, Lda.

Apartado 1

3754-001 Barrô (Águeda)

Portugal

4 – System of assessment and checking for regularity of applicable performance:

System 4

5 – Performance declared:

<u>Essential characteristics</u>	<u>Performance</u>	<u>Standard</u>
Reaction to fire	A1 and A1 _{FL}	EN 14411:2012 (Group Bla GL or UGL)
Release of dangerous substances, for: - Cadmium (Cd) - Lead (Pb)	NPD NPD	
Bending strength: - Thickness < 7,5mm ≥ 7,5mm	> 1500 N > 2000 N	
Bond strength/adhesion, for:	NPD	
Slippage	NPD	
Resistance to thermal shock	Resistant	
Tactility:	NPD	
Durability, for: - Internal use - External use (resistance to frost)	Compliant Compliant	

NPD – Non-Stated Performance. It is stated for each case, on client's request.

Performance statement issued under the full responsibility of the manufacturer, identified in point 3.

Laboratory Responsible



Nuno Mano

23th September 2022