

revigres®

# BIM LIBRARY MANUAL

---

JUNE 2022  
Version 02

StratBIM®

## TABLE OF CONTENTS

DOCUMENT VERSIONS .....	3
BIM LIBRARY MANUAL .....	4
01. Introduction .....	4
02. Library Description .....	4
03. Compatible Versions .....	4
04. Objects Characteristics .....	4
05. Inserting the material library .....	5
06. Insertion of Families .....	6
07. Properties of objects .....	10
08. Quantification of materials .....	11
09. Final Considerations .....	11

## DOCUMENT VERSIONS

V.00	01/03/2019	First published version.
V.01	30/04/2019	Revision of the material's library in all RVT files and in the library ADKS file; Placement of AEBBC, AERBC, AIBBC e AIRBC corner families corrected.
V.02	21/06/2022	Cromatic collection update.

# BIM LIBRARY MANUAL

## 01. Introduction

This BIM Library Manual aims to support the installation and use of BIM Objects related to products developed and marketed by **REVIGRÉS**, seeking to help AEC Industry - Architecture, Engineering and Construction technicians in their decision making process.

## 02. Library Description

The presented library was developed for AUTODESK®2019 version or newer and refers to CHROMATIC collection marketed by REVIGRÉS.

Included in this library are all the typologies of the mentioned collection in the colors, finishes and commercialised formats, namely:

- **AEBBC** (external round angle with cove base);
- **AERBC** (external straight angle with cove base);
- **AIBBC** (internal round angle with cove base);
- **AIRBC** (internal straight angle with cove base);
- **Base**;
- **BR** (bars);
- **Chevron**;
- **Cube**;
- **DG** (carved round top step);
- **Half**;
- **RB** (round top bullnose);
- **RBBC** (round top bullnose with cove base);
- **RRBC** (straight top bullnose with cove base);
- **TC** (Corner);
- **Trio**.

## 03. Compatible Versions

The library is compatible with the AUTODESK REVIT®2019 version or newer.


## 04. Objects Characteristics

The objects are created in the respective categories, so that they can be used according to their actual application. This way, all objects relating to floor and wall coverings are created in the category *Floor* and *Wall* objects - *system families*. Only the interior and exterior footer corners are created as *loadable families*. For the development of step objects, it is possible to create them with *Floor* objects as well as *Stairs*, using *profile families* simultaneously.


The objects are shown identified with nominal measures, but are represented with their actual measurements (caliber 06), adding 1mm to this measurement for accounting of the joint.

## 05. Inserting the material library

The created objects have associated materials, which, for the purpose of representation, have images that give it its characteristics with respect to color, shape and finish. In order for the program to map correctly, all images must be downloaded from the file **REVIGRES-CROMATICA-Material-Images.zip**. You will then need to include the path to that folder in the list of paths to map material textures. To do this, you will have to go to **FILE / OPTIONS**:




Then, in the **RENDERING** section, add the path to the list of additional paths:




This way, we ensure that all the necessary images of the materials and objects are properly mapped for during the rendering process.

## 06. Insertion of Families

In the case of objects belonging to *System families*, namely those relating to wall and floor coverings, they must be loaded from one project file (RVT) to another. Thus, to transfer the elements of the Wall or Floor category, you must open the REVIGRES file with the desired CHROMATIC typology, as well as the project file that you want to transfer the REVIGRES objects, and go to **MANAGE / TRANSFER PROJECT STANDARDS**:




You must then activate the object type that you want to transfer. In the case of floors, the **Floor Types** option must be chosen, in the case of wall coverings, the **Wall Types** option:




This method applies to the transfer of elements of the typology: **Base, BR, Chevron, Cube, Half, TC e Trio**.

The footer objects, referring to the **RB, RRBC** and **RBBC** typologies of the REVIGRES CHROMATIC series, are developed as objects of the *Wall Sweep* category. Therefore, in order to load these objects for a project, the file **REVIGRES-CROMATICA-RB\_RRBC\_RRBC-R19-v00.rvt** must be opened first. You can then take the needed objects from the file, for this go back to **MANAGE / TRANSFER PROJECT STANDARDS**, as mentioned above. Then choose the *Wall Sweep Types* option:



In order to be applied, simply activate the specific command to place *Wall Sweeps* in **ARCHITECTURE / WALL / WALL: SWEEP**:




The **DG** objects are made in the *Floor* category so that they can be applied together as a floor. However, they are also prepared to be applied directly to **Stair** type objects. To use this typology as a floor, the way to load objects is like the one explained for the Base, BR and similar series, through the **MANAGE / TRANSFER PROJECT STANDARDS** tab and choosing the **Floor Types** option. To use directly on Stair objects, you must first load the **REVIGRES-CROMATICA-DG-TREAD\_PROFILE.rfa** family into the project, which contains all possible profiles for DG type


parts. Then, as before, go to **MANAGE / TRANSFER PROJECT STANDARDS** and activate the options:

- **Materials**
- **Stair Types**


After the information regarding the materials and the type of stairs being loaded in the design, a staircase with the characteristics of the objects of the DG typology can be created. To do this, you must activate the **ARCHITECTURE / STAIR** command:




After choosing the family and type of stairs you want, press **EDIT TYPE** in the properties dialog box:




In the **Construction** section, click the value displayed in the **Run Type** parameter:



Next, you will be able to choose the type of **Run Type** you want, within the depths of the blanket that the DG type of the CROMÁTICA series allows:




After choosing the type of object of the **DG** typology, it is necessary to change some parameters, so that it is represented conveniently. First, the material for the step itself will be chosen in the *Materials and Finishes* section in the parameter **Tread Material**:




Then, the thickness of the step blanket according to the thickness of the piece, which can be seen in the following table (measured in cm), should be chosen:

	MATTNAT	MATTRECT	POL	SOFT
30x30	7.7	8.5	8.0	8.5
30x60	-	8.5	8.0	8.5
30x120	-	9.8	9.3	9.8
45x90	-	10.5	9.8	10.5
60x60	-	8.5	8.0	8.5
60x120	-	9.8	9.3	9.8


Meantime, once the **REVIGRES-CROMÁTICA-DG-TREAD\_PROFILE.rfa** family has been previously loaded, we can select the profile to be used in the **Treads** section, choosing the profile in the **Tread Profile** parameter:



Corner objects **AEBBC**, **AERBC**, **AIBBC**, and **AIRBC** are loadable families, so they must be loaded through the tab **INSERT / LOAD FAMILY**:



These can be found as *Wall Based* objects, so you will need to create a Wall objective to be able to be placed in the project.



## 07. Properties of objects

The objects have been developed in-depth and extensively. Thus, all objects have information concerning the manufacturer with respect to applicable international standards, namely:

- Anti Slip resistance\_ DIN 51130;
- PTV classification\_ BS7976-2:2002;
- Slip resistance value through the pendulum method\_ UNE-ENV 12633: 2003;
- Types of use\_1-5;
- UPEC classification;
- Variations in Hue\_1-3.

Data	
AntiSlipResistance	R9
PTV	PTV 36+
SlipResistanceValuePendulumMethod	Class1
TypesOfUse	5
UPEC	U4P4E3C2
VariationInHue	V1

All objects also have the manufacturer's reference, so that it can be easily referenced, as well as other relevant information:

General	
BIM Modeler URL	www.stratbim.com
CE marking	YES
Manufacturer URL	www.revigres.pt
Publication date	03/2019
Reference	312B137S31
Region Africa	ALL
Region Antarctica	ALL
Region Asia	ALL
Region Europe	ALL
Region Middle East	ALL
Region North America	ALL
Region Oceania	ALL
Region South America	ALL
Version	V00

The objects are also classified according to the international classification systems most commonly used in the AEC industry.

IFC Parameters	
CSI Masterformat 2014 Code	09 30 13
CSI Masterformat 2014 Title	Ceramic Tiling
CSI Unifomat II Code	C3010
CSI Unifomat II Title	Wall Finishes
IfcExportAs	IfcCorevingType
IfcExportType	CLADDING
NBS Reference Code	80-96-19
NBS Reference Description	Ceramic tiles
Uniclass 1.4 Code	L533
Uniclass 1.4 Description	Tiles and blocks (rigid)
Uniclass 2.0 Code	PR-80-96-19
Uniclass 2.0 Description	Ceramic tiles
Uniclass 2015 Code	Pr_35_93_96_19
Uniclass 2015 Description	Ceramic tiles
UNSPSC Code	30131704
UNSPSC Description	Ceramic tiles or flagstones
Analysis Results	

## 08. Quantification of materials

All the files related to the various typologies of the CROMÁTICA collection have pre-configured tables with the parameters related to the coating, its respective manufacturer's reference, parameters related to the applicable standards, as well as quantification parameters of the applied coating and the number of pieces applicable. The number of pieces is calculated by dividing the area of coating by the area of a piece, so that, depending on the geometry of the area to be coated, an increase of about 10% should be considered for breaks and cuts.

## 09. Final Considerations

Future revisions to the current version of the library will be made available on the REVIGRÉS website. Any question regarding them should be reported by email to [bimsupport@revigres.pt](mailto:bimsupport@revigres.pt).

# revigres®

Founded in 1977, Revigrés is a world reference in ceramics, specialized in the production of wall and floor tiles.

Revigrés headquarters is located in Barrô (Águeda) and its commercial building – opened in 1997 -, is a project by Architect Álvaro Siza Vieira, the first winner of the Pritzker Prize in Portugal. In addition to the showroom at headquarters, Revigrés also has a showroom in Lisbon (Saldanha).

It is present in more than 50 countries and maintains a close relationship and collaboration with professionals in the national and international market, being frequently selected to be associated with works of great impact, to carry out special, personalized and exclusive projects.

A highlight is the Basilica La Sagrada Familia, in Barcelona, to which it has developed, exclusively, a wide variety of colors from the Chromatic Collection, one of the most complete porcelain stoneware collections worldwide.

Revigrés is the only Portuguese company in the subsector of ceramic wall and floor tiles with a four-time certification of its integrated management systems (SGI), in the following references: Quality; Environment; Social Accountability; Research; Development and Innovation.

Developed by

StratBIM®

[info@stratbim.com](mailto:info@stratbim.com)



[www.stratbim.com](http://www.stratbim.com)