PERFORMANCE STATEMENT

002DDGP

1 –Unique identification code for product / type:

Glazed or unglazed dry pressed ceramic tiles, with water absortion less than 0.5% ($E_b \leq 0.5\%$).

2 – Use:

For internal or external, floor and wall.

3 –Name and address of manufacturer:

Revigrés, Indústria de Revestimentos de Grés, Lda.
Apartado 1
3754-001 Barrô (Águeda)
Portugal

4 –System of assessment and checking for regularity of applicable performance:

System 4

5 – Performance declared:

Essential characteristics	Performance	Standard
Reaction to fire	A1 and A1 $_{FL}$	EN 14411:2012 (Group BIa GL or UGL)
Release of dangerous substances, for: - Cadmium (Cd) - Lead (Pb)	 NPD NPD	
Bending strengh: - Thickness < 7,5mm ≥ 7,5mm	 > 1500 N > 2000 N	
Bond strenght/adhesion, for:	NPD	
Slippage	NPD	
Resistance to thermal shock	Resistant	
Tactility:	NPD	
Durability, for: - Internal use - External use (resistance to frost)	 Compliant Compliant	

NPD – Non Stated Performance. It is stated for each case, on client's request.

This performance statement has been issued under the responsibility of the manufacturer identified in point 3.

Quality Department

Rui Vasco
27.06.2014

REVIGRÉS - Indústria de Revestimentos de Grés, Lda
Apartado 1 • 3754-001 BARRÔ (Águeda) • Portugal
Tel. +351 234 660 100 Fax +351 234 666 555
www.revigres.com revigres@revigres.pt